

IN THE CLAIMS:

Please CANCEL Claims 2, 41, 43, 44, 45, 46, and 48 without prejudice to or waiver of the subject matter contained therein.

Please AMEND Claims 1 and 34 and add Claims 54-66, as follows. All claims currently pending in this application are being reproduced below:

1. (Currently Amended) A supporting structure for supporting an optical element, said supporting structure comprising:

a first supporting member for supporting the optical element;

a second supporting member arranged in an outer diameter side of the first supporting member for supporting the first supporting member; and

an at least one elastic member placed between the first supporting member and the second supporting member in ~~the~~ a radial direction of the optical element, ~~an inner diameter side of the~~ said at least one elastic member being connected to ~~the~~ said first supporting member and said ~~while an outer diameter side of the elastic member being connected to the~~ second supporting member, and said at least one ~~the~~ elastic member being elastically deformable in the radial direction, wherein the value of the thermal expansion coefficient of said first supporting member is between those of the optical element and said second supporting member.

2. (Cancelled).

3. (Original) A structure according to Claim 1, wherein the thermal expansion coefficient difference between the optical element and the first supporting member is smaller than the thermal expansion coefficient difference between the optical element and the second supporting member.

4. (Original) A structure according to Claim 3, wherein the optical element is made from quartz and the first supporting member is made from an alloy including nickel.

5. (Original) A structure according to Claim 3, wherein the optical element is made from quartz and the first supporting member is made from one of a cordierite ceramic material including magnesium oxide and silicon oxide, a ceramic material including alumina and silicon nitride, and Zerojule (TM) which is glass with low thermal expansion.

6. (Original) A structure according to Claim 3, wherein the optical element is made from fluorite and the first supporting member is made from an alloy including copper.

7. (Previously Amended) A structure according to Claim 3, wherein the optical element is made from fluorite and the first supporting member is made from one of an alloy of iron-chromium-nickel and an alloy including aluminum as a principal ingredient.

7
8.

(Original) A structure according to Claim 1, wherein the values of the thermal expansion coefficient of the optical element, the first supporting member, and the second supporting member are substantially the same.

12
9.

(Previously Amended) A supporting structure for supporting an optical element, said supporting structure comprising:

a first supporting member for supporting the optical element;

a second supporting member arranged in an outer diameter side of the first supporting member for supporting the first supporting member; and

an elastic member placed between the first supporting member and the second supporting member in the radial direction of the optical element, an inner diameter side of the elastic member being connected to the first supporting member while an outer diameter side of the elastic member being connected to the second supporting member, the elastic member being elastically deformable in the radial direction,

wherein the elastic member is a plate-shaped spring member in which both ends thereof are connected to the first supporting member and the central portion thereof is connected to the second supporting member, and wherein a plurality of the plate-shaped spring members are arranged in a peripheral portion of the first supporting member at substantially equal intervals.

8.
10. (Original) A structure according to Claim 1, wherein the elastic member is made from the same material as that of the first supporting member.

9.
11. (Original) A structure according to Claim 1, wherein the optical element is one of a lens, a mirror, and an optical element to which diffraction is applied.

10.
12. (Previously Amended) An exposure apparatus comprising:
an illuminating optical system for illuminating a reticle with a light beam from a light source; and
a projection optical system for projecting a light beam from the reticle on a wafer,
wherein at least one of the illuminating optical system and the projection optical system have a supporting structure for supporting an optical element according to Claim 1.

11.
13. (Previously Amended) A method for manufacturing semiconductor devices, said method comprising:
performing an exposing step by an exposure apparatus according to Claim 12.

Claims 14 through 24 were previously cancelled.

13
25.

(Previously Amended) An exposure apparatus comprising:

an illuminating optical system for illuminating a reticle with a light beam from a light source; and

a projection optical system for projecting a light beam from the reticle onto a wafer,

wherein at least one of the illuminating optical system and the projection optical system have a supporting structure for supporting an optical element according to Claim

13
9.

14
26.

(Previously Amended) A method for manufacturing semiconductor

devices, said method comprising:

performing an exposing step by an exposure apparatus according to Claim. 13
25.

Claims 27 through 33 were previously cancelled.

15
34.

(Currently Amended) A supporting structure for supporting an a

plurality of optical elements element, said supporting structure comprising:

a plurality of first supporting members for respectively supporting the plurality of optical elements; and

~~a plurality of first supporting members for respectively supporting the plurality~~ of optical elements; and

a plurality of second supporting members for respectively supporting the plurality of first supporting members via a plurality of elastic structures having elasticity in the radial direction of the optical element,

wherein the radial clearance between one of the optical elements and a corresponding one of said the first supporting members contains adhesive.

35. (Original) A structure according to Claim 34, wherein the plurality of first supporting members do not contact each other.

Claims 36 through 37 were previously cancelled.

38. (Original) A structure according to Claim 34, wherein the radial clearance between the optical element and the first supporting member is filled with adhesive along the whole circumference of the optical element.

39. (Original) A structure according to Claim 34, wherein the radial clearance between the optical element and the first supporting member is discontinuously filled with adhesive in a plurality of portions on the circumference of the optical element.

~~19~~
~~40.~~ (Original) A structure according to Claim ~~34~~³⁵, wherein the thermal expansion coefficient of the first supporting member is an intermediate value between thermal expansion coefficient values of the optical element and the second supporting member.

41. (Cancelled)

~~41~~
~~42.~~ (Previously Amended) A structure according to Claim ~~34~~³⁵, wherein the thermal expansion difference between the optical element and the first supporting member is less than the thermal expansion difference between the optical element and the second supporting member.

43. (Cancelled)

44. (Cancelled)

45. (Cancelled)

46. (Cancelled)

~~46~~
~~47.~~ (Previously Amended) A supporting structure for supporting an optical element, said supporting structure comprising:

a plurality of optical elements;
a plurality of first supporting members for respectively supporting the plurality of optical elements; and
a plurality of second supporting members for respectively supporting the plurality of first supporting members via structures having elasticity in the radial direction of the optical element,
wherein the elastic member is made from a plate-shaped spring member in which both ends of the spring member are connected to the first supporting member and the central portion thereof is connected to the second supporting member, and wherein a plurality of the plate-shaped spring members are arranged in the periphery of the first supporting member at substantially equal intervals.

48. (Cancelled)

49. (Original) A structure according to Claim 34, wherein the optical element is one of a lens, a mirror, and an optical element to which diffraction is applied.

50. (Previously Amended) An exposure apparatus comprising:
an illuminating optical system for illuminating a reticle with a light beam from a light source; and

a projection optical system for projecting a light beam from the reticle on a wafer,

wherein at least one of the illuminating optical system and the projection optical system have a supporting structure for supporting an optical element according to Claim 34.

51. (Previously Amended) A method for manufacturing semiconductor devices, said method comprising:

performing an exposing step by an exposure apparatus according to Claim 50.

52. (Previously Added) An exposure apparatus comprising:
an illuminating optical system for illuminating a reticle with a light beam from a light source; and
a projection optical system for projecting a light beam from the reticle on a wafer,

wherein at least one of the illuminating optical system and the projection optical system have a supporting structure for supporting an optical element according to Claim 47.

53. (Previously Added) A method for manufacturing semiconductor devices, said method comprising:

performing an exposing step by an exposure apparatus according to Claim ²⁵52.

Please add Claims 54-66 as follows:

²⁷
~~54.~~ (New) A supporting structure for supporting an optical element, said supporting structure comprising:

- a first supporting member for supporting the optical element;
- a second supporting member arranged in an outer diameter side of the first supporting member for supporting the first supporting member; and
- a plurality of elastic members placed between said first supporting member and said second supporting member in a radial direction of the optical element, said plurality of elastic members being connected to said first supporting member and said second supporting member, and each of said elastic members including a spring member elastically deformable in the radial direction.

²⁸
²⁷
~~55.~~ (New) A structure according to claim ²⁷54, wherein the spring member has a plate-shaped spring member.

²⁹
~~56.~~ (New) An exposure apparatus comprising:

- an illuminating optical system for illuminating a reticle with a light beam from a light source; and

a projection optical system for projecting a light beam from the reticle on a wafer,

wherein at least one of the illuminating optical system and the projection optical system have a supporting structure for supporting an optical element according to Claim 54.

30
57. (New) A method for manufacturing semiconductor devices, said method comprising:

performing an exposing step by an exposure apparatus according to Claim 56. 39

32
58. (New) A supporting structure for supporting a plurality of optical elements, said supporting structure comprising:

a plurality of first supporting members each of which respectively supports each of the plurality of optical elements; and

a plurality of second supporting members each of which respectively supports each of the plurality of first supporting members via a plurality of spring members having elasticity in the radial direction of the optical element.

33 34
59. (New) A structure according to claim 58, wherein the spring member has a plate-shaped spring member.

324
60.

(New) An exposure apparatus comprising:

an illuminating optical system for illuminating a reticle with a light beam from a light source; and

a projection optical system for projecting a light beam from the reticle on a wafer,

wherein at least one of the illuminating optical system and the projection optical system have a supporting structure for supporting an optical element according to Claim

32
58.

31
61.

(New) A method for manufacturing semiconductor devices, said

method comprising:

performing an exposing step by an exposure apparatus according to Claim 56.

35
62.

(New) A supporting structure for supporting an optical element, said

supporting structure comprising:

a first supporting member for supporting the optical element, wherein a radial clearance between the optical element and the first supporting member contains adhesive; and

a second supporting member for supporting the first supporting member via a plurality of elastic members having elasticity in a radial direction of the optical element.

³⁵
~~63.~~ (New) A structure according to claim ~~62~~, wherein each of the elastic members has a spring member.

³⁶
~~64.~~ (New) A structure according to claim ~~63~~, wherein each of the elastic members has a plate-shaped spring member.

³⁸
~~65.~~ (New) An exposure apparatus comprising:
an illuminating optical system for illuminating a reticle with a light beam from a light source; and
a projection optical system for projecting a light beam from the reticle on a wafer,
wherein at least one of the illuminating optical system and the projection optical system have a supporting structure for supporting an optical element according to Claim

³⁵
~~62.~~

³⁹
~~66.~~ (New) A method for manufacturing semiconductor devices, said method comprising:
performing an exposing step by an exposure apparatus according to Claim ³⁵~~65~~.